

NEW Products


Symbol	Meaning of symbol	Symbol	Meaning of symbol
W	Stand for All White LED series	CC	Stand for Constant Current version
H.W	Stand for 2835 High output white LED series	CV	Stand for Constant Voltage version
S.W	Stand for 2835 Super high output white LED series	CC.H	Stand for high light efficiency constant current version
Fu.W	Stand for 2835 Full-Spectrum (TM-30-15) white LED series	CV.H	Stand for high light efficiency constant voltage version
Fu.S.W	Stand for 2835 Super High Output Full-Spectrum (TM-30-15) Series	CC.L	Stand for super long constant current version
CCT	Stand for Color temperature adjustable LED strips	150mA	2835 White LED max 150mA, Actual use is less than 60mA
>90	Stand for CRI, Such as CRI>80 / CRI>90 / CRI>95,etc.	XIXIX	Stand for there are several parameters to choose
R	Stand for colors, Such as R/G/B/Y/A/RGB/RGBX/RGBXX,etc.	/	Stand for this parameter value is not for reference

Note: S.W \ Fu.S.W \ warranty 5 years; H.W \ Fu.W \ R \ G \ B \ Y \ A warranty 3 years.

Patented: Intelligent identification of input voltage Version


Descriptions

This LED strip light suitable for solar cells with voltage rise and fall


Descriptions						COLOR
						Option
LEDs Q'ty/m	60	Model No.:	DL-F28A30V24-SMC-*-4775	CRI option:	>80; >90; >95	
		Input Voltage:	SMC 12V~24V	One Cut:	3LEDs/50mm	
SMD Type	2835	Power option:	4.8W	PCB width:	10mm	
		Lumen/W:	157 lm	IP Rate option:	IP20/IP65/IP67/IP68	
Length (Reel)	10m	Lumen/m:	705 lm	Color option:	W\R\G\B\Y\A	R
		White LED:	H.W\S.W\Fu.W\Fu.S.W	Version:	CC.H	G
						B

Tunable by Switch CCT Adjustable LED strip light version



Descriptions

Descriptions						COLOR
						Option
LEDs Q'ty/m	168	Model No.:	DL-F28A84V24-CCT-*-5214	CRI option:	>80; >90; >95	
		Voltage :	24V	One Cut:	14LEDs/83.33mm	
SMD Type	2835	Typ. Power:	19.2W	PCB width:	12mm	
		Lumen / W:	PW:163lm; WW:109lm; P+W:135lm	IP option:	IP20/IP65/IP67/IP68	
Length (Reel)	5m	Lumen / m:	PW:1608lm; WW:1051lm; P+W:2601lm	Warranty:	3 years	>90 CCT
		Color Temp.:	CCT (2600-6500K)	Version:	CCT Tunable by Switch	>95 CCT


Tunable by PWM CCT Adjustable LED strip light version

Descriptions						COLOR	
High light efficiency15 meters one side powered, Keep the same brightness from the beginning to the end						Option	
LEDs Q'ty/m	168	Model No.:	DL-F28A84V24-CCT-*-5462	CRI option:	>80; >90; >95		>90 CCT
		Voltage :	24V	One Cut:	14LEDs/83.33mm		
SMD Type	2835	Typ. Power:	11W	PCB width:	12mm		>95 CCT
		Lumen / W:	PW:132lm; WW:139lm; P+W:138lm	IP option:	IP20/IP65/IP67/IP68		
Length (Reel)	5m	Lumen / m:	PW: 1459lm; WW: 1577lm; P+W:962lm	Warranty:	3 years		
		Color Temp.:	CCT (2600-6500K)	Version:	CCT Tunable by PWW		


Features: High Light Efficiency and Super Long LED Strips

Descriptions						COLOR	
High light efficiency15 meters one side powered, Keep the same brightness from the beginning to the end						Option	
LEDs Q'ty/m	112	Model No.:	DL-F28A56V24-CC.H-*-4490	CRI option:	>80; >90; >95		H.W
		Input Voltage:	24V	One Cut:	7LEDs/62.5mm		S.W
SMD Type	2835	Power option:	16.8W	PCB width:	10mm		Y/A
		Lumen/W:	155 lm	IP Rate option:	IP20/IP65/IP67/IP68		R
Length (Reel)	15m	Lumen/m:	2600	Color option:	W\R\G\B\Y\A		G
		White LED:	H.W\S.W\Fu.W\Fu.S.W	Version:	CC.H		B
LEDs Q'ty/m	112	Model No.:	DL-F56A56V24-CC.L-*-4925	CRI option:	>80; >90		H.W
		Input Voltage:	DC24V	One Cut:	7LEDs/62.5mm		S.W
SMD Type	2835	Power option:	9.6W(15m) \ 15.4W(10m)	PCB width:	12mm		Y/A
		Lumen/W:	162 lm	IP Rate option:	IP20/IP65/IP67		R
Length (Reel)	15m	Lumen/m:	1608 lm	Color option:	W\R\G\B\Y\A		G
		White LED:	H.W	Version:	CC.L		B



DC48V Super Long 50m CC version

Descriptions						COLOR	
50 meters one side Powered, Keep the same brightness from the beginning to the end.						Option	
LEDs Q'ty/m	144	Model No.:	DL-F28A72V48CC.L-*-16011	CRI option:	>80; >90; >95		H.W
		Input Voltage:	DC48V	One Cut:	24LEDs/166.66mm		S.W
SMD Type	2835	Power option:	5.8W	PCB width:	12mm		Y/A
		Lumen/W:	145 lm	IP Rate option:	IP20/IP65/IP67/IP68		R
Length (Reel)	50m	Lumen/m:	874 lm	Color option:	W\R\G\B\Y\A		G
		White LED:	H.W\S.W\Fu.W\Fu.S.W	Version:	CC.L		B


DC24V Super Long 30m CC version

Descriptions						COLOR	
30 meters one side Powered, Keep the same brightness from the beginning to the end.						Option	
LEDs Q'ty/m	60	Model No.:	DL-F28A30V24-CC.L-B10-*-16012	CRI option:	>80; >90; >95		H.W
		Input Voltage:	DC24V	One Cut:	10LEDs/166.66mm		S.W
SMD Type	2835	Power option:	2.9W	PCB width:	10mm		Y/A
		Lumen/W:	121 lm	IP Rate option:	IP20/IP65/IP67/IP68		R
Length (Reel)	30m	Lumen/m:	363 lm	Color option:	W\R\G\B\Y\A		G
		White LED:	H.W\S.W\Fu.W\Fu.S.W	Version:	CC.L		B



Tunable by One Loop CCT Adjustable LED Strip Light Version

Descriptions							COLOR
							Option
LEDs Q'ty/m	288	Model No.:	DL-F28A144V24-CCT-*--5493	CRI option:	>80; >90; >95		>90 CCT
		Voltage :	24V	One Cut:	16LEDs/55.55mm		
SMD Type	2835	Typ. Power:	18W	PCB width:	12mm		>95 CCT
		Lumen / W:	PW:130lm; WW:117lm; P+W:123lm	IP option:	IP20/IP65/IP67/IP68		
Length (Reel)	5m	Lumen / m:	PW:2299lm; WW:2057lm; P+W:2158lm	Warranty:	3 years		
		Color Temp.:	CCT (2600-6500K)	Version:	One Loop CCT		
LEDs Q'ty/m	420	Model No.:	DL-F22A210V12-CCT-*--4831	CRI option:	>80; >90 ; >95		>90 CCT
		Voltage :	12V	One Cut:	6LEDs/14.28mm		
SMD Type	2216	Typ. Power:	9.6W/m	PCB width:	8mm		>95 CCT
		Lumen / W:	PW:111lm; WW:101lm; P+W:105lm	IP option:	IP20/IP65/IP67/IP68		
Length (Reel)	5m	Lumen / m:	PW:1083lm; WW:989lm; P+W:1022lm	Warranty:	3 years		
		Color Temp.:	CCT (2600-6500K)	Version:	One Loop CCT		

SMD2110 Narrow FPC Version

Descriptions							COLOR
							Option
LEDs Q'ty/m	350	Model No.:	DL-F21A175V24-*--5380	CRI option:	>90 ; >95		W
		Input Voltage:	24V	PCB width:	4mm		Ra>90
SMD Type	2110	Power option:	8W	IP option:	IP20/IP65/IP67/IP68		R
		Lumen/W:	115 lm	Color option:	WW\NW\PW\R\G\B		G
Length (Reel)	5m	Lumen/m:	875 lm	Warranty:	3 years	B	
		One Cut:	7LEDs/20mm	Version:	CV	Y/A	

High Light Efficiency CV2835 Version

Descriptions							COLOR
							Option
LEDs Q'ty/m	256	Model No.:	DL-F28A128V24-CV.H-*--5166	CRI option:	>80 ; >90; >95		H.W
		Input Voltage:	DC24V	One Cut:	8LEDs/31.25mm		S.W
SMD Type	2835	Power/m:	28.8W	PCB width:	12mm		Y/A
		Lumen/W:	151 lm	IP Rate option:	IP20/IP65/IP67		R
Length (Reel)	3m	Lumen/m:	4355 lm	Color option:	W\R\G\B\Y\A	G	
		White LED:	H.W\S.W\Fu.W\Fu.S.W	Version:	CV.H	B	
LEDs Q'ty/m	256	Model No.:	DL-F28A128V24-CV.H-*--5229	CRI option:	>80 ; >90; >95		H.W
		Input Voltage:	DC24V	One Cut:	8LEDs/31.25mm		S.W
SMD Type	2835	Power/m:	28.8W	PCB width:	15mm		Y/A
		Lumen/W:	163 lm	IP Rate option:	IP20/IP65/IP67		R
Length (Reel)	3m	Lumen/m:	4510 lm	Color option:	W\R\G\B\Y\A	G	
		White LED:	H.W\S.W\Fu.W\Fu.S.W	Version:	CV.H	B	





High Light Efficiency

CC2835 Version

Descriptions

COLOR

Option

LEDs Q'ty/m	192	Model No.:	DL-F28A96V24-CC.H-*-5289	CRI option:	>80; >90; >95		H.W
		Input Voltage:	24V	One Cut:	8LEDs/41.66mm		S.W
SMD Type	2835	Power option:	17.2W/m	PCB width:	12mm		Y/A
		Lumen/W:	182 lm	IP Rate option:	IP20/IP65/IP67/IP68		R
Length (Reel)	5m	Lumen/m:	4282 lm	Color option:	W\R\G\B\Y\A		G
		White LED:	H.W\S.W\Fu.W\Fu.S.W	Version:	CC.H		B
LEDs Q'ty/m	256	Model No.:	DL-F28A128V24-CC.H-*-5247	CRI option:	>80; >90; >95		H.W
		Input Voltage:	24V	One Cut:	8LEDs/31.25mm		S.W
SMD Type	2835	Power option:	28.8W	PCB width:	12mm		Y/A
		Lumen/W:	176 lm	IP Rate option:	IP20/IP65/IP67/IP68		R
Length (Reel)	5m	Lumen/m:	5069 lm	Color option:	W\R\G\B\Y\A		G
		White LED:	H.W\S.W\Fu.W\Fu.S.W	Version:	CC.H		B





CCT Adjustable LED Strip

CV2110 version

Descriptions

COLOR

Option

LEDs Q'ty/m	616	Model No.:	DL-F22A308V24-CCT-*-5378	CRI option:	>90; >95		>90 CCT	
		Voltage (DC) :	24V	One Cut:	14LEDs/22.72mm			>95 CCT
SMD Type	2110	Typ. Power:	17.5W / 21W	PCB width:	10mm			
		Lumen / W:	PW:101lm; WW:89lm; P+W:93lm	IP option:	IP20\IP65\IP67\IP68			
Length (Reel)	5m	Lumen / m:	PW:900lm; WW:785lm; P+W: 1593lm	Warranty:	3 years			
		Color Temp.:	CCT (2600-6500K)	Version:	CCT			





Side View + Top View

CV3014 version

Descriptions

COLOR

Option

LEDs Q'ty/m	208	Model No.:	DL-F34A104V24-SV-*-3608	CRI:	>80; >90; >95		W	
		Voltage :	DC 24V	One Cut:	8LEDs/38.46mm			R
SMD Type	3014	Typ. Power:	16W	PCB width:	10mm			
		Lumen / W:	116 lm	IP Rate:	IP20/IP65/IP67/IP68		B	
Length (Reel)	5m	Lumen / m:	1838 lm	Warranty:	3 & 5 years		Y	
		Color option:	W/R/G/B/Y/A	Version:	Side View		A	



COB

Flexible LED Strip Light

Descriptions

COLOR

Option

LEDs Q'ty/m	576	Model No.:	DL-COBA288V24-8mm-*	CRI option:	>90; >95		WW/NW/PW CRI>90
		Input Voltage:	DC24V	One Cut:	288LEDs/50mm		
SMD Type	COB	Power option:	10W	PCB width:	8mm		
		Lumen/W:	110 lm	IP Rate option:	IP20/IP65/IP67		
Length (Reel)	5m	Lumen/m:	1100 lm	Color option:	W\R\G\B\Y\A		
		White LED:	COB	Version:	CC.L		